B-Micro Washer Extractors

8 Programmable Cycles – Factory Settings

- Normal/Hot — 1 hot wash, 3 cold rinses
- Normal/Warm — 1 warm wash, 3 cold rinses
- Perm Press/Warm — 1 warm wash, 3 cold rinses
- Perm Press/Cold — 1 cold wash, 3 cold rinses
- Quick Wash/Hot — 1 hot wash, 2 cold rinses
- Quick Wash/Warm — 1 warm wash, 2 cold rinses
- Heavy Soil/Hot — 1 longer hot wash, 3 cold rinses
- Delicate/Cold — 1 cold wash, 2 cold rinses

- Customer-Friendly LED Display Shows Vend Price, Coin Countdown, Water Level Achieved And Cycle Time Remaining
- 3 Owner-Programmable Water Levels
- 2 Quick Wash Cycles To Get Your Customers In And Out FAST
- Cycle Counter — Non-Resettable For Up To 9999 Cycles
- Diagnostic Capabilities
- Cycle Status Indicator Lights
- Customize Your Cycles With Up To 4 Washes And 4 Rinses
- 3-Year Limited Parts Warranty

Speed Queen®

A Passion to Lead

Washer-Extractor Specifications

		SC20	SC25	SC30	SC40	SC60	SC80
Capacity - lb (kg)		20 (9)	25 (11.3)	30 (13.6)	40 (18)	60 (27)	80 (36)
Width - in (mm)		26" (660)	26" (660)	29" (737)	30 5/8" (778)	34 1/16" (865)	41 1/2" (1054)
Depth - in (mm)*		29 13/16" (757)	33 15/16" (859)	34 13/16" (884)	40 3/16" (1021)	42 13/16" (1087)	51 5/8" (1312)
Height - in (mm)		42" (1067)	45" (1143)	45 7/8" (1165)	47 7/8" (1216)	50" (1270)	56" (1422)
Cylinder Diameter - in (mm)		21" (533)	21" (533)	24" (610)	26 1/4" (667)	30" (762)	36" (914)
Cylinder Volume - cu. ft. (liters)		2.76 (78.1)	3.76 (106)	4.19 (119)	6.34 (180)	9.0 (255)	12.4 (351)
Door Opening Size - in (mm)		11 5/8" (295)	11 5/8" (295)	14 11/32" (364)	16 1/4" (413)	16 1/4" (413)	18 1/4" (463)
Door Bottom to Floor - in (mm)		14 3/8" (366)	14 3/8" (366)	14" (356)	14 1/2" (368)	18 1/2" (470)	21 5/8" (549)
G-Factor (High Extract)		83.1	83.1	73.3	89.8	93.8	40/85/140
Wash Speed - RPM		57	57	49	51	44	22/40
High Extract - RPM		528	529	464	491	469	280/408/524
Water Inlet Conn. - in (mm)		3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)
Drain Diameter - in (mm)		2 3/8" (60)	2 3/8" (60)	2" (52)	3" (76)	3" (76)	3" (76)
Drain Height to Floor - in (mm)		4 1/2" (114)	4 1/2" (114)	4" (102)	4 3/4" (121)	5" (127)	5 3/4" (146)
Motor - HP (kW) Wash		.18 (.13)	.25 (.19)	.25 (.19)	.40 (.30)	.55 (.41)	N/A
Motor - HP (kW) Extract		1.0 (.75)	1.4 (1.04)	1.4 (1.04)	1.8 (1.3)	2.7 (2.01)	5 (3.7)
Voltage/Hz/Phase** Circuit Breaker-FLA amp	B	110-120/60/1 • 20-15	N/A	N/A	N/A	N/A	N/A
	C	380-415/50/3 • 15-4	380-415/50/3 • 15-4	380-415/50/3 • 15-4	380-415/50/3 • 15-5	380-415/50/3 • 15-4	N/A
	D	220-240/50/3 • 15-5	220-240/50/3 • 15-6	220-240/50/3 • 15-6	220-240/50/3 • 15-8	220-240/50/3 • 20-7	N/A
	E	220-240/50/1 • 20-10	220-240/50/1 • 20-10	220-240/50/1 • 20-10	N/A	N/A	N/A
	F	N/A	N/A	N/A	N/A	N/A	N/A
	J	200/50/3 • 15-5	200/50/3 • 15-5	200/50/3 • 15-5	200/50/3 • 20-8	200/50/3 • 20-8	N/A
	N	N/A	N/A	N/A	N/A	N/A	440-480/50-60/3 • 15-4
	O**	208-240/60/3 • 15-5	208-240/60/3 • 15-7	208-240/60/3 • 15-7	208-240/60/3 • 20-7	208-240/60/3 • 20-10	N/A
	P	N/A	N/A	N/A	N/A	N/A	380-415/50-60/3 • 15-4
	Q**	N/A	N/A	N/A	N/A	N/A	200-240/50-60/3 • 15-7
	X	N/A	N/A	N/A	N/A	200-240/50-60/1-3 • 20-9	N/A
	Y	208-240/60/1 • 15-10	208-240/60/1 • 20-10	208-240/60/1 • 20-10	208-240/60/1 • 30-14	N/A	N/A
Shipping Dimensions - in (mm)	H	51" (1295)	56 1/2" (1435)	56 1/2" (1435)	56 1/2" (1422)	58 1/2" (1486)	62 1/2" (1588)
	W	29" (737)	32" (813)	32" (813)	32" (813)	36" (914)	48" (1219)
	D	32 1/2" (826)	41" (1041)	41" (1041)	41" (1041)	44 1/2" (1130)	56" (1422)
Net Weight - lb (kg)		353 (160)	427 (194)	496 (225)	686 (311)	811 (368)	1346 (611)
Shipping Weight - lb (kg)		373 (169)	448 (203)	519 (235)	710 (322)	838 (380)	1420 (644)
Agency Approvals***		CE, ETL, ETLc	CE, ETL, ETLc	CE, ETL, ETLc	CE, ETL, ETLc	CE, ETL, ETLc	CE, ETL, ETLc

* Overall depth includes drain pipe and door handle.

** Standard domestic voltage 208–240/60/3. Circuit breaker and amp draw data shown is for standard voltage models without auxiliary heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines. All CE approved models available in 50 hz 20-60 models.

*** Agency approvals may vary depending on configuration. Consult factory for details. Steam connection requires 1/2" N.P.T.

For the most accurate information, the insallation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

©Copyright 2008 Alliance Laundry Systems LLC

www.speedqueen.com

Speed Queen®
Alliance Laundry Systems